ThinkPad universal usb-c smart dock

Powered by Microsoft Azure Sphere.



A SMARTER WAY TO WORK.

More than just a hub, the Lenovo™ ThinkPad® Universal USB-C Smart Dock is a leader in our new series of docks offering a smarter way to work. A bridge to a more intelligent future, the dock features universal USB-C compatibility, incredible performance for commercial users, a secure cloud-based management solution for IT managers, and it's all powered by Microsoft Azure Sphere.

WHY YOU NEED THINKPAD UNIVERSAL USB-C SMART DOCK



11+ Possibilities, 1 Cable.

Get more from your workday by adding 11+ expansion possibilities in a single quick-release cable for maximum efficiency. Expand your creative potential with access to multiple 4K monitors, and blazing-fast data transfers with USB-C and USB-A. Plus, rapid-charing for your laptops up to 100W so you can remain energized at all times.



Universal Dock Compatibility

Boost the value of your investment with the broad compatibility of the ThinkPad Universal USB-C Smart Dock. Supporting both Thunderbolt^{\mathbb{M}} 3 and 4, USB 4 \mathbb{M} and USB-C, and extended compatibility with a wide range of brands and Multi-OS notebooks, you'll be ready to overcome any obstacle.



Streamlined Management

Break free from the old docking paradigm and streamline your management workflow with a range of time-saving innovations. With the ThinkPad Universal USB-C Smart Dock ready, you can remotely update its firmware without a PC connected, remotely manage ports, conduct data analytics, utilize diagnostic tools, and keep your system safe with Microsoft Azure Sphere security solution.

Powered by Microsoft Azure Sphere.





DESIGN

Weight

Net Weight

1 x K-lock Slot



SPECIFICATIONS

PERFORMANCE

Solution

USB Type-C™ DP Alt Mode Micosoft Azure Sphere

Connectivity

1 m USB-C Cable

Video Port

2 x DisplayPort™ 1.4 1 x HDMI™ 2.0

USB Port

3 x USB-A 3.1 Gen 21 (10 Gbps, 1 x always-on charging) 2 x USB-A 2.01 1 x USB Type-C[™] (10 Gbps, 5V/3A)

Video Resolution

Maximum: 4K2

Number of Displays

Maximum: 3

Stereo/Microphone Combo

Max. Charging to Notebook

100W

Kensington® Lock Slots

Dimensions (L x M x H)

(inches): 6.73" x 3.15" x 1.18"

(mm) : 171 x 80 x 30

1 x NanoSaver Lock Slot

CONNECTIVITY

Ethernet

RJ45

- PXE Boot, WOL, MAC Address Pass-through Supported

:Starting at 0.51 kg (1.1 lbs)

Package Weight: Starting at 1.12 kg (2.5 lbs)

INFORMATION

Part Number (PN)

40B20135XX

Compatible OS

Windows Linux Chrome MAC OS

Compatible System

Thunderbolt™ 4 USB 4™ Thunderbolt™ 3 USB Type-C™

Cloud Service

Microsoft Azure

Security Platform

Microsoft Azure Sphere

IT Console

Web-based Management Service

ENERGY STAR®

Yes

Ship Group

ThinkPad Universal USB-C Smart Dock 135W Power Adapter and Power Cord

1 m USB-C Cable

Warranty and Setup Poster

² The real resolution will depend on your PC and Monitor capability.





ACCESSORYSMARTFIND.LENOVO.COM

Lenovo reserves the right to alter product offerings and specifications at any time, without notice. Lenovo makes every effort to ensure accuracy of all information but is not liable or responsible for any editorial, photographic, or typographic errors. All images are for illustration purposes only. For full Lenovo product, service, and warranty specifications, visit www.lenovo.com. Lenovo makes no representations or warranties regarding third-party products or services. Trademarks: The following are trademarks or registered trademarks of Lenovo: Lenovo, the Lenovo logo, Rescue and Recovery, ThinkPad, ThinkCentre, ThinkServer, ThinkServer, ThinkVantage, and ThinkVision. Other company, product, and service names may be trademarks or service marks of others. Battery life (and recharge times) will vary based on many factors, including system settings and usage. Visit www.lenovo.com/lenovo/us/en/safecomp/ periodically for the latest information on safe and effective computing. ©2021 Lenovo. All rights reserved.

¹ Depending on many factors such as the processing capability of peripheral devices, file attributes, and other factors related to system configuration and operating environments, the actual transfer rate using the various USB connectors on this device will vary and is typically slower than the data rates as defined by the respective USB specifications: - 5 Gbit/s for USB 3.1 Gen 1; 10 Gbit/s for USB 3.1 Gen 2 & 20 Gbit/s for USB 3.2.